

TANK NUMBER:

BARGE "IB 951"

INGRAM BARGE COMPANY

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

ST. LOUIS SHIP HULL NO. 4263

0 FEET	1 FEET	2 FEET	3 FEET	4 FEET	5 FEET	6 FEET	7 FEET	8 FEET	9 FEET	10 FEET	11 FEET	12 FEET	13 FEET
IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0	IN. 0
0	0	0	0	0	0	0	0	0	0	0	0	0	0
13.12	16.64	21.18	25.80	27.83	26.25	25.74	25.45	25.25	25.05	24.84	24.63	24.42	24.21
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
1	1	1	1	1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10	10	10	10	10
11	11	11	11	11	11	11	11	11	11	11	11	11	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13	13	13	13	13	13	13

CAPACITY IN: 42-GALLON BARRELS

*CAPACITY BELOW STRIKE POINT.

GAUGE HEIGHT: 15'-2 1/2" (TOP EDGE FLAME SCREEN REST IN EXPANSION TRUNK HATCH)

CALIBRATED: 9/18/78

W. J. Martin

CHAS. MARTIN
Inspectors
of Petroleum, Inc.
INDEPENDENT LICENSED INSPECTION
MEMBERS OF ASTM AND API

FORM NO. 10-11-11
 (Max. MARTIN) Inspectors
 of Petroleum, Inc.
 INDEPENDENT LICENSED INSPECTION
 MEMBERS OF API AND A.P.I.

INGRAM BARGE COMPANY
BARGE "IB 951"

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

ST. LOUIS SHIP HULL NO. 4263

0 FEET	1 FEET	2 FEET	3 FEET	4 FEET	5 FEET	6 FEET	7 FEET	8 FEET	9 FEET	10 FEET	11 FEET	12 FEET	13 FEET
IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.	IN.
0	261.14	513.90	766.67	0	1,019.43	1,272.20	1,524.97	1,777.74	2,030.51	2,283.27	2,536.04	2,788.81	3,041.58
1/2	18.23	266.40	519.16	771.93	1,029.97	1,282.73	1,535.50	1,788.27	2,041.04	2,293.81	2,546.57	2,804.61	3,062.64
1	23.23	271.67	524.43	777.20	1,035.23	1,288.00	1,540.77	1,793.54	2,046.30	2,299.07	2,551.84	2,809.87	3,071.28
3/4	28.23	276.93	529.70	782.46	1,040.50	1,293.27	1,546.03	1,798.80	2,051.57	2,304.34	2,557.11	2,809.87	3,071.28
2	53.25	303.26	556.03	808.79	1,061.56	1,314.33	1,567.10	1,819.87	2,072.63	2,325.40	2,578.17	2,830.94	3,083.71
1/2	58.25	308.52	561.29	814.06	1,066.83	1,319.60	1,572.36	1,825.13	2,077.90	2,330.67	2,583.44	2,836.20	3,088.97
1/4	63.26	313.79	566.56	819.33	1,072.09	1,324.86	1,577.63	1,830.40	2,083.17	2,335.93	2,588.70	2,841.47	3,094.24
3/4	68.26	319.06	571.82	824.59	1,077.36	1,330.13	1,582.90	1,835.66	2,088.43	2,341.20	2,593.97	2,846.74	3,099.50
3	73.26	324.32	577.09	829.86	1,082.63	1,335.39	1,588.26	1,841.03	2,093.79	2,346.57	2,599.33	2,852.00	3,104.77
1/2	78.26	329.59	582.36	835.12	1,087.89	1,340.66	1,593.43	1,846.20	2,098.96	2,351.73	2,604.50	2,857.27	3,110.04
1/4	83.27	334.85	587.62	840.39	1,093.16	1,345.93	1,598.69	1,851.46	2,104.23	2,357.00	2,609.77	2,862.53	3,115.30
3/4	88.27	340.12	592.89	845.66	1,098.42	1,351.19	1,603.96	1,856.73	2,109.50	2,362.26	2,615.03	2,867.80	3,120.57
4	93.27	345.39	598.15	850.92	1,103.69	1,356.46	1,609.23	1,861.99	2,114.76	2,367.53	2,620.30	2,873.07	3,125.83
1/2	98.28	350.65	603.42	856.19	1,108.96	1,361.72	1,614.49	1,867.26	2,120.03	2,372.80	2,625.56	2,878.33	3,131.10
1/4	103.28	355.92	608.69	861.45	1,114.22	1,367.99	1,619.76	1,872.53	2,125.29	2,378.06	2,630.83	2,883.60	3,136.37
3/4	108.54	361.18	613.95	866.72	1,119.49	1,372.26	1,625.02	1,877.79	2,130.56	2,383.33	2,636.10	2,888.86	3,141.63
5	113.79	366.45	619.22	871.99	1,124.75	1,377.52	1,630.29	1,883.06	2,135.83	2,388.59	2,641.36	2,894.13	3,146.90
1/2	119.05	371.72	624.48	877.25	1,130.02	1,382.79	1,635.56	1,888.32	2,141.09	2,393.86	2,646.63	2,899.40	3,152.16
1/4	124.30	376.98	629.75	882.52	1,135.29	1,388.05	1,640.82	1,893.59	2,146.36	2,399.13	2,651.89	2,904.66	3,157.43
3/4	129.56	382.25	635.02	887.78	1,140.55	1,393.32	1,646.09	1,898.86	2,151.62	2,404.39	2,657.16	2,909.93	3,162.70
6	134.82	387.51	640.28	893.05	1,145.82	1,398.59	1,651.35	1,904.12	2,156.89	2,409.66	2,662.43	2,915.19	3,167.96
1/2	140.07	392.78	645.55	898.32	1,151.08	1,403.85	1,656.62	1,909.39	2,162.16	2,414.92	2,667.69	2,920.46	3,173.23
1/4	145.33	398.05	650.81	903.58	1,156.35	1,409.12	1,661.89	1,914.65	2,167.42	2,420.19	2,672.96	2,925.73	3,178.49
3/4	150.58	403.31	656.08	908.85	1,161.62	1,414.38	1,667.15	1,919.92	2,172.69	2,425.46	2,678.22	2,930.99	3,183.76
7	155.84	408.58	661.35	914.11	1,166.88	1,419.65	1,672.42	1,925.19	2,177.95	2,430.72	2,683.49	2,936.26	3,189.03
1/2	161.10	413.84	666.61	919.38	1,172.15	1,424.92	1,677.68	1,930.45	2,183.22	2,435.99	2,688.76	2,941.52	3,194.29
1/4	166.37	419.11	671.88	924.65	1,177.41	1,430.18	1,682.95	1,935.72	2,188.49	2,441.25	2,694.02	2,946.79	3,199.56
3/4	171.63	424.38	677.14	929.91	1,182.68	1,435.45	1,688.22	1,940.98	2,193.75	2,446.52	2,699.29	2,952.06	3,204.82
8	176.90	429.64	682.41	935.18	1,187.95	1,440.71	1,693.48	1,946.25	2,199.02	2,451.79	2,704.55	2,957.32	3,210.09
1/2	182.16	434.91	687.68	940.44	1,193.21	1,445.98	1,698.75	1,951.52	2,204.28	2,457.05	2,709.82	2,962.59	3,215.36
1/4	187.43	440.17	692.94	945.71	1,198.48	1,451.25	1,704.01	1,956.78	2,209.55	2,462.32	2,715.09	2,967.85	3,220.62
3/4	192.69	445.44	698.21	950.98	1,203.74	1,456.51	1,709.28	1,962.05	2,214.82	2,467.58	2,720.35	2,973.12	3,225.89
9	197.96	450.71	703.47	956.24	1,209.01	1,461.78	1,714.55	1,967.31	2,220.08	2,472.85	2,725.62	2,978.39	3,231.15
1/2	203.22	455.97	708.74	961.51	1,214.28	1,467.04	1,719.81	1,972.58	2,225.35	2,478.12	2,730.88	2,983.65	3,236.42
1/4	208.49	461.24	714.01	966.77	1,219.54	1,472.31	1,725.08	1,977.85	2,230.61	2,483.38	2,736.15	2,988.92	3,241.69
3/4	213.75	466.50	719.27	972.04	1,224.81	1,477.58	1,730.34	1,983.11	2,235.88	2,488.65	2,741.42	2,994.18	3,246.51
10	219.02	471.77	724.54	977.31	1,230.07	1,482.84	1,735.61	1,988.38	2,241.15	2,493.91	2,746.68	2,999.45	3,251.34
1/2	224.28	477.04	729.80	982.57	1,235.34	1,488.11	1,740.88	1,993.64	2,246.41	2,499.18	2,751.95	3,004.72	3,256.17
1/4	229.55	482.30	735.07	987.84	1,240.61	1,493.37	1,746.14	1,998.91	2,251.68	2,504.45	2,757.21	3,009.98	3,260.99
3/4	234.81	487.57	740.34	993.10	1,245.87	1,498.64	1,751.41	2,004.18	2,256.94	2,509.71	2,762.48	3,015.25	3,264.94
11	240.08	492.83	745.60	998.37	1,251.14	1,503.91	1,756.67	2,009.44	2,262.21	2,514.98	2,767.75	3,020.51	3,268.89
1/2	245.34	498.10	750.87	1,003.64	1,256.40	1,509.17	1,761.94	2,014.71	2,267.48	2,520.24	2,773.01	3,025.78	3,272.84
1/4	250.61	503.37	756.13	1,008.90	1,261.67	1,514.44	1,767.21	2,019.97	2,272.74	2,525.51	2,778.28	3,031.05	3,276.79
3/4	255.87	508.63	761.40	1,014.17	1,266.94	1,519.70	1,772.47	2,025.24	2,278.01	2,530.78	2,783.54	3,036.31	3,279.87

CAPACITY IN: 42-GALLON BARRELS

*CAPACITY BELOW STRIKE POINT.

GAUGE HEIGHT: 15'-2 1/2" (TOP EDGE FLAME SCREEN REST IN EXPANSION TRUNK HATCH)

9/18/78 CALIBRATED

J. J. Martin